



| Terminal | |
|----------|----------|
| No. | Pin Name |
| 1 | FG |
| 2 | VSS |
| 3 | VDD |
| 4 | NC |
| 5 | /RES |
| 6 | /RD |
| 7 | /WR |
| 8 | /CS |
| 9 | A0 |
| 10 | DB0 |
| 11 | DB1 |
| 12 | DB2 |
| 13 | DB3 |
| 14 | DB4 |
| 15 | DB5 |
| 16 | DB6 |
| 17 | DB7 |
| 18 | BLA |
| 19 | /WAIT |
| 20 | NC |

- Note:
- *1. LCD Display Type : FSTN, Positive, Transflective
 - *2. Viewing Direction : 6H
 - *3. Duty : 1/128
 - *4. Operating Voltage : 5.0V
 - *5. Backlight Color : White
 - *6. Built in LCD Controller : S1D13700(or equivalent)
 - *7. Operating Temperature : -20°C ~ 70°C
 - *8. Storage Temperature : -30°C ~ 80°C

| | | | | |
|--------------------------------|---------------|-----------------|------------|--|
| C | | | | |
| B | | | | |
| A | | | | |
| Rev | Note | Date | | |
| Dwg Title LM19501E Outline Dwg | | | | |
| Dwg No. | MK-001492-1-1 | Date 2006-11-15 | | |
| Scale | Tol. | Unit | Paper Size | |
| 3/2 | ±0.5 | mm | A3 | |
| Approved | Checked | Drawn Linyan | | |
| TOPWAY | | | | |