



K1 Terminal		
No.	Name	(*)10
1	VSS	
2	VDD	
3	V0	
4	/WR	
5	/RD	
6	/CS	
7	RS	
8	/RST	
9	DB0	
10	DB1	
11	DB2	
12	DB3	
13	DB4	
14	DB5	
15	DB6	
16	DB7	
17	BUSY	
18	VDOUT	
19	BLA	
20	BLK	

- Note:
- *1. Display Type : STN, Negative, Transmissive
 - *2. Viewing Direction : 6H
 - *3. Duty : 1/240
 - *4. Backlight Color : White
 - *5. Backlight Supply : 5.0V
 - *6. Operating Voltage : 5.0V
 - *7. Operating Temperature : -20°C~70°C
 - *8. Storage Temperature : -30°C~80°C
 - *9. Controller : RA8806 or equivalent
 - *10. An external VR(25K to 50K) must be connected for Contrast Control
 - *11. Environmental Safe Standard : RoHS

C		
B		
A	Typing Correction	Cheng Yuanyuan 2009-05-12
Rev	Note	Date
Dwg	Title	LM2088RFW outline Dwg
Dwg	No.	MK-002817a-1-1 Date 2009-04-09
Scale	Tol.	Unit
1/1	±0.5	mm
Approved	Checked	Paper Size A3
		Drawn Zhou Huifang

